

AP-Series Label Applicators



AP 362e LABEL APPLICATOR

AP-Series Label Applicators are perfect semi-automatic labelling solution for cylindrical containers as well as many tapered containers, including bottles, cans, jars and tubes.

Set-up and operation is fast and easy. Just:

1. Set the guides
2. Place your container in the machine
3. Press the footswitch and your label is applied

The built-in spring-loaded pressure arm makes sure labels are applied firmly and without wrinkles.

With an AP-Series Label Applicator you'll apply labels faster and more accurately - helping to speed up your production and sell more of your products!



AP 360e
LABEL APPLICATOR

Apply Labels Fast and Accurately

With an AP-Series Label Applicator you'll be able to apply labels at speeds of up to 1200 per hour. Labels are perfectly applied without wrinkles, giving your finished products a highly professional look.

AP-Series Label Applicators are an ideal accessory to LX- or CX - Series label printers. The applicators can also apply roll-fed, pressure-sensitive labels produced by most other flexographic, offset and digital presses.

Two Models Available

AP360e is the base model. It quickly and efficiently applies single labels at a time.

AP362e is an advanced model. It can apply one or two different labels to a single container. A built-in LED counter and memory for up to nine front-to-back label offsets is also included.

Features

- * Quick set-up and easy operation
- * Accurately applies labels to the front (AP360e) or front and back (AP362e) with variable spacing
- * Fast - labels are applied at 5.3" (135mm) per second - up to 1200 containers per hour
- * Compact size - fits on most desks and counter tops
- * Professionally designed - one of the only semi-automatic label applicators available with UL, CSA and FCC safety and emissions certifications
- * Industrial strength - built with heavy-duty sheet metal and steel for long life



Specifications

Container width:	1" to 9.4" (25.4mm to 238mm)
Container Diameter:	15mm to 170mm (0.6" to 6.7")
Container shape:	Cylindrical and many tapered
Supply roll diameter:	Up to 203mm (8")
Media liner width:	25.4mm to 213mm (1" to 8.375")
Supply roll core:	51.8mm to 76.2mm (2" to 3" I.D.)
Electrical ratings:	12VDC, 5.0A
Power requirements:	100-240VAC, 50/60 Hz, 60 watts
Agency certifications:	UL, UL-C, CE, FCC Class A
Weight:	7.26 Kg (16lbs.)
Dimensions:	340mmW x 266mmH x 328mm D (13.4"W x 8.9"H x 12.9"D)

**Please contact our sales department
for a quotation or further information.**



Unit 4, Block 4, Chapelhall Industrial Estate, Airdrie, ML6 8QH
Tel: 01236 754075 Fax: 01236 768604
www.labeltec.co.uk

